



VRX 00 230

VRX00230 36,39Qli / 8.000 lb 12 volt

Specifiche: Features

Forza trazione Rated line pull	8000 lbs(3629kgs)
Motore Motor	Series wound 3.6KW/4,8hp(12V);4,8KW/6,4hp(24V)
Rapporto cambio Gear reduction ratio	210:1(12V), 150:1(24V)
Rapporto cambio Gear reduction ratio	Ø5/16"*95'(Ø8mm*29m)
Misura tamburo lun. Drum size(Dia.*L).	Ø2.48"*9"(Ø63mm*228mm)
Dim.totali lun.lar.alt. Overall dimensions(*L*W*H)	22.4"*7.1"*6.8"(570mm*180mm*173mm)
Dim.totali lun.lar.alt. Overall dimensions(*L*W*H)	22.4"*7.1"*10.63"(570mm*180mm*270mm)(Up-SettingType)
Struttura montaggio Mounting bolt pattern	10"*4.5"(254mm*114.3mm)
Peso Weight	76.7 lbs(34.8kg)
Peso	80.5 lbs(36.5kg)(Up-Setting Type)

Weight

Trazione, velocità, ampere, volts (1a tensione) Pull, Speed, Amperes, Volts(First layer)

Trazione (libr.Kg.) Line Pull Ibs(kgs)	Velocità piedi/min (m/min) Line Speed ft/mit(m/min)	Corrente Current A		
	12V DC	24V DC	12V DC	24 VDC
0	24(7.3)	35(10.5)	80	50
2000(907)	13(3.8)	19(5.8)	150	90
4000(1814)	9(2.7)	12.8(3.9)	220	135
6000(2722)	7(2.1)	10(3.0)	270	170
8000(3629)	5.6(1.7)	6.6(2.0))	320	210

Trazione e portata corda in tensione Line Pull And Rope Capacity In Layer

Tensione corda Layer	Forza trazione Rated Line Pull Ibs(kgs)	Corda totale su tamburo Total Rope On Drum ft(m)
1	8000(3629)	19.6(6.0)
2	6500(2948)	42.6(13.0)
3	5500(2495)	68.9(21.0)
4	4800(2177)	95.0(29.0)

Avviso: Caratteristiche Standard, non usare per trasporto persone..

Notice: Standard features do not use for people carriage.